




High electric ray sparkle control. Suitable for all types of general lighting applications. A lighting solution compatible with all MR16 retrofit LED lamps and Ø51mm LED modules. Tool-free module or lamp installation. Various frame and body color options to match the design. Easy locking mechanism for body mounting and maintenance. Maintenance-free engineering plastic body. Long-lasting LED product with aluminum outer body. Long-lasting and lightweight design. No special tools required for ceiling mounting.

- Outer Diameter - Ø80mm
- Height - 170mm
- Weight - 355g
- Flame-retardant ABS Body Material
- 15°, 24°, 38° Beam Angle Options
- Three-phase, Single-phase, and DALI Socket Options



Description	Power (W)	Lumen (lm)	CCT (Kelvin)	CRI	Angle	Current (mA) /Voltage (V)
Pulse Beam Spot	8,0 W	750 Lm	2700 K	80+	15°, 24°, 38°	200 mA
Pulse Beam Spot	8,0 W	800 Lm	3000 K	80+	15°, 24°, 38°	200 mA
Pulse Beam Spot	8,0 W	850 Lm	4000 K	80+	15°, 24°, 38°	200 mA
Pulse Beam Spot	11,0 W	950 Lm	2700 K	80+	15°, 24°, 38°	250 mA
Pulse Beam Spot	11,0 W	1000 Lm	3000 K	80+	15°, 24°, 38°	250 mA
Pulse Beam Spot	11,0 W	1050 Lm	4000 K	80+	15°, 24°, 38°	250 mA

Product Series

CRIve CCT (Kelvin)

Product Power

IRA001.008.827.XX.AA.Y

Driver Control Option

1 = On Off
2 = Faz Dim
3 = 0-10V
4 = DALI

Product Color Options

Angle Options

(15°/24°/38°/VW/FL/AS/etc.)

50 Black + Black	54 Black + Gold	58 White + Gold	62 Gray + White	66 Gri + Krom
51 White + White	55 Black + Rose	59 White + Rose	63 Gray + Black	67 Gray + Platin
52 Black + White	56 Black + Krom	60 White + Krom	64 Gray + Rose	
53 White + Black	57 Black + Platin	61 White + Platin	65 Gray + Gold	